

CHEMLUBE® 813-22 CHAIN LUBRICANT

Applications:

Chemlube 813-22 has been designed for use in chain applications. Although this is a relatively new chain lubricant, it incorporates the experience and knowledge gained through applications of earlier production lubes.

Performance Benefits:

- Synthetic mixture
- Prevents rust and oxidation
- Excellent anti-wear properties
- Base fluid combination provides natural cleaning and detergency

CHEMLUBE®

TYPICAL PROPERTIES	TEST METHOD	Chemlube 812-68
ISO Grade	ASTM D2422	22
Viscosity @ 40°C,cSt	ASTM D445	23.3
Viscosity @ 100°C,cSt	ASTM D445	4.5
Viscosity Index	ASTM D2270	105
Flash Point, °C/°F	ASTM D92	210/410
Pour Point, °C/°F	ASTM D97	-12/-10
Specific Gravity	ASTM D1298	0.88
Pounds per gallon		7.69

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE
IN
USA



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com