

CHEMLUBE 228 RC SYNTHETIC BASED COMPRESSOR OIL

Applications:

Chemlube 228 RC is designed for 6,000 – 8,000 hours of use in rotary screw compressors. This product is a specially formulated PAO (polyalphaolefin) synthetic blend for use in a wide variety of air compressors. Chemlube 228RC is used where maximum seal, paint, and plastic compatibility is required.

Characteristics:

- Good thermal and oxidative stability
- Compatible with most seals, plastics & rubbers
- Wide operating temperature range
- Non-detergent
- Extended drain intervals reduces oil disposal, thus increasing cost effectiveness

CHEMLUBE®

TYPICAL PROPERTIES	TEST METHOD	Chemlube 228 RC
ISO Grade	ASTM D2422	46
SAE Grade	SAE J-300	20
Viscosity @ 40°C,cSt	ASTM D445	40.45
Viscosity @ 100°C,cSt	ASTM D445	6.82
Viscosity Index	ASTM D2270	126
Flash Point, °C/°F	ASTM D92	250/488
Pour Point, °C/°F	ASTM D97	-45/-49
Copper Corrosion	ASTM D130	1b
Foaming Sequences I, II, III	ASTM D892	Nil
Demulsibility	ASTM D1401	Excellent
Evaporation, %	ASTM D972	1.0
Specific Gravity	ASTM D1298	0.86

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE
IN
USA



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com