

## CHEMLUBE® BF2 and BF6 SYNTHETIC BARRIER FLUIDS

### Applications:

Chemlube BF2 and BF6 are formulated with premium polyalphaolefin (PAO) base oils to obtain fluidity at low temperatures and oxidative stability at high temperatures. These NSF approved barrier fluids will lubricate and cool the seal face of double and tandem mechanical seals. Chemlube BF2 and BF6 do not contain additives or impurities that may poison or negatively affect process fluids or catalysts. These barrier fluids are not for use with EPDM or EPR elastomers. They are compatible with most other commonly used seal materials.

### Typical Industrial Applications:

- Barrier Fluid
- Food Processing (H-1)

### Performance Benefits:

- Low pour point
- Excellent oxidation stability
- Complies with FDA 21 CFR 178.3570 H-1

TYPICAL PROPERTIES	TEST METHOD	Chemlube BF2	Chemlube BF6
Viscosity @ 40°C,cSt	ASTM D445	5	31
Viscosity @ 100°C,cSt	ASTM D445	1.7	5.9
Viscosity Index	ASTM D2270	---	138
Flash Point, °C/°F	ASTM D92	157/315	235/455
Pour Point, °C/°F	ASTM D97	-59/-74	-54/-65
Specific Gravity	ASTM D1298	0.80	0.82

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)