

CHEMLUBE® PLUS SERIES SYNTHETIC COMPRESSOR LUBRICANTS

Applications:

The Chemlube Plus Series are made with a very thermally and oxidatively stable polyol ester (POE) blend. These fully synthetic premium lubricants are formulated to form less varnish under high temperature applications and to be more resistant to acidic intake air than the polyalkylene glycol coolants. Under normal operating conditions you can expect to obtain up to 11,000 hours of lubricant service life in rotary screw compressors.

Typical Industrial Applications:

- Rotary Screw Compressors
- Rotary Vane Compressors
- Centrifugal Compressors
- Vacuum Pumps

Performance Benefits:

- Outstanding thermal and oxidative stability
- Extended drain intervals reduces oil disposal
- Wide operating temperature range
- Excellent anti-wear protection
- Compatible with most compressor oils
- Improved safety - High flash point

TYPICAL PROPERTIES	TEST METHOD	Chemlube Plus 32	Chemlube Plus 10	Chemlube Plus 68
ISO Grade	ASTM D2422	32	46	68
Viscosity @ 40°C,cSt	ASTM D445	32	44.4	66
Viscosity @ 100°C,cSt	ASTM D445	6.3	7.3	9.9
Viscosity Index	ASTM D2270	125	126	132
Flash Point, °C/°F	ASTM D92	240/464	240/464	240/464
Pour Point, °C/°F	ASTM D97	-50/-58	-50/-58	-50/-58
Foaming Sequences I, II, III	ASTM D892	Nil	Nil	Nil
Demulsibility	ASTM D1401	Excellent	Excellent	Excellent
Evaporation, %	ASTM D972	1.0	1.0	1.0
Specific Gravity	ASTM D1298	0.88	0.89	0.89

CHEMLUBE®

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE
IN
USA



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com