

## CHEMLUBE® 10W-30, 10W-40, 10W50 and 20W-50 SYNTHETIC BLEND DIESTER-BASED MOTOR OILS

### Applications:

Chemlube 10W-30, 10W-40, 10W50 and 20W-50 are multi-grade premium motor oils formulated from a premium synthetic diester blend. These superior motor oils are recommended for light duty diesel (API CF) and gasoline engines wherever API SN and ILSAC GF-5 is required. Chemlube 20W-50 is recommended when a heavier synthetic motor oil is needed.

### Performance Benefits:

- Low evaporation rate resulting in up to 50% reduction in oil consumption
- Great combination of sub-zero starting ease with a proven 30°F cooling effect on the hottest days
- Film strength exceeds all premium mineral oil based lubricants resulting in minimal wear
- Full compatibility with mineral oil

TYPICAL PROPERTIES	TEST METHOD	Chemlube 10W-30	Chemlube 10W-40	Chemlube 10W-50	Chemlube 20W-50
SAE Grade	SAE J-300	10W-30	10W-40	10W-50	20W-50
Viscosity @ 40°C,cSt	ASTM D445	53.6	67.8	95.4	107.8
Viscosity @ 100°C,cSt	ASTM D445	9.8	12.5	16.63	17.9
Viscosity Index	ASTM D2270	180	193	189	185
Flash Point, °C/°F	ASTM D92	234/454	223/434	228/444	228/444
Pour Point, °C/°F	ASTM D97	-45/-49	-42/-43	-41/-42	-44/-43
Weight %					
Calcium		0.214	0.214	0.214	0.214
Nitrogen		0.102	0.102	0.102	0.102
Zinc		0.085	0.085	0.085	0.085
Phosphorus		0.077	0.077	0.077	0.077
Molybdenum, ppm		79	79	79	79
Specific Gravity	ASTM D1298	0.87	0.87	0.89	0.90

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)

MADE  
IN  
USA



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)