

## OMNILUBE® WO 680 FOOD GRADE GEAR LUBRICANT

### Applications:

Omnilube WO 680 Food Grade Gear Oil is a white oil based lubricating oil which meets the requirements to be classified as H-1 for incidental contact with food. It has been engineered to provide superior lubrication protection to gear sets, bearings and pumps in applications where food contact may occur.

Omnilube WO 680 Food grade lubricant meets the requirements of FDA regulation 21 CFR 178.3570.

### Typical Industrial Applications:

- Bearings and gears.
- Chain applications.

**OMNILUBE®**

TYPICAL PROPERTIES	TEST METHOD	Omnilube WO 680
ISO Grade	ASTM D2422	680
Viscosity @ 40°C,cSt	ASTM D445	790
Viscosity @ 100°C,cSt	ASTM D445	52.5
Viscosity Index	ASTM D2270	120
Flash Point, °F	ASTM D92	230/446
Pour Point, °C	ASTM D97	-6/21
Copper Corrosion	ASTM D130	1b
Specific Gravity	ASTM D1298	0.99

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)

**MADE  
IN  
USA**



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)