

OMNILUBE® WO COOKER VALVE OIL

HIGH TEMPERATURE WATER RESISTANT OIL



Applications:

Omnilube WO Cooker Valve Oil is made from highly refined, purified USP Grade white mineral oils that are colorless, odorless, and tasteless. Omnilube WO Cooker Valve Oil fully complies with USP and FDA requirements as per 21 CFR 172.878. This premium cooker valve oil is designed for use in Cookers and Sterilizers where high temperatures and high humidity are present. Omnilube WO Cooker Valve Oil also provides protection for bearing, slides and operating valves.

Typical Industrial Applications:

- Manzel Lubricators
- Microvalve Systems
- Flooded Live Steam
- Cookers
- Sterilizers
- Bearings
- Slides
- Operating Valves
- Food Processing (H-1)

Performance Benefits:

- Complies with FDA 21 CFR 178.3570 H-1

OMNILUBE®

TYPICAL PROPERTIES	TEST METHOD	Omnilube WO Cooker Valve Oil
ISO Grade	ASTM D2422	150
Viscosity @ 40°C,cSt	ASTM D445	142
Viscosity @ 100°C,cSt	ASTM D445	14.5
Viscosity Index	ASTM D2270	100
Flash Point, °C/°F	ASTM D92	226/504
Pour Point, °C/°F	ASTM D97	-35/-31
Foaming Sequence, I, II, III	ASTM D892	Nil

03/10

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com

MADE
IN
USA



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com