

## ULTRACHEM® AIR TOOL 22 AIR TOOL LUBRICANT

### Applications:

Ultrachem Air Tool 22 lubricant is an air tool lubricant specifically designed to provide superior lubrication for rotary and reciprocating types of air tools. Application is done by feeding the lubricant directly through an air line lubricator or by applying oil directly into the air tool through quick-coupling air line connections.

### Typical Industrial Applications:

- Air Motors
- Impact Wrenches
- Grinders
- Reamers
- Drills
- Chipping Hammers

### Performance Benefits:

- Compatible with petroleum oils and PAO's
- Designed specifically for air tools
- Protects against rust
- Provides wear protection
- Formulated for improved stability



TYPICAL PROPERTIES	TEST METHOD	Ultrachem Air Tool 22
ISO Grade	ASTM D2422	22
Viscosity @ 40°C,cSt	ASTM D445	22.9
Viscosity @ 100°C,cSt	ASTM D445	4.1
Viscosity Index	ASTM D2270	77
Flash Point, °C/°F	ASTM D92	194/380
Pour Point, °C/°F	ASTM D97	-40/-40
Specific Gravity	ASTM D1298	0.86

03/10

#### HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

#### TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at [info@ultracheminc.com](mailto:info@ultracheminc.com)

MADE  
IN  
USA



900 Centerpoint Blvd.  
New Castle, DE 19720  
P.....302-325-9880  
F.....302-325-0335  
[info@ultracheminc.com](mailto:info@ultracheminc.com)