

Ultrachem AWF MULTI-GRADE HYDRAULIC OIL

Applications:

Ultrachem AWF is a multi-grade anti-wear hydraulic fluid. It has been designed for year-round service in mobile equipment operating at very low or widely varying ambient temperatures. It is recommended for use in mobile hydraulic equipment, including cherry pickers, backhoes, shovels, hydraulic cranes and extension ladders. It can be used in stationary hydraulic equipment operating at abnormally low temperatures. This product provides excellent lubricity and wear protection, oxidation and corrosion protection and detergency for system cleanliness. Meets or exceeds leading pump and system manufacturer's specifications such as Delaval, Denison, Dynex, Moog, Racine, Rexroth, Sundstrand, Towler, Vickers and U.S. Steel.

Performance Benefits:

- Wide temperature operating range.
- Anti-wear protection
- Detergency for system cleanliness
- Excellent oxidation and corrosion protection

| TYPICAL PROPERTIES | TEST METHOD | Ultrachem AWF |
|------------------------|-------------|---------------|
| SAE Grade | | 5W-20 |
| Viscosity @ 40°C,cSt | ASTM D445 | 47 |
| Viscosity @ 100°C,cSt | ASTM D445 | 7.8 |
| Viscosity Index | ASTM D2270 | 135 |
| Flash Point, °C/°F | ASTM D92 | 215/420 |
| Pour Point, °C/°F | ASTM D97 | -42/-45 |
| Copper Corrosion | ASTM D130 | 1B |
| Foaming Seq., I,II,III | D892 | Pass |
| Acid # | D664 | 0.80 |
| Dielectric Strength | D877 | 35+ |
| Zinc, % wt. | --- | 0.04 |

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



4/12

900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com