

OMNILUBE PRODUCT DATA SHEET







SYNTHETIC FOOD GRADE LUBRICANT

Applications:

Omnilube Air Line FG is a fully synthetic food grade oil that is formulated with the highest quality polyalphaolefin (PAO) base oil to meet the lubrication requirements of air line equipment. This NSF approved lubricant is formulated with high performance antioxidants and anti-wear additives to meet the challenges of industrial environments. This product provides lubrication for all air line equipment used in food processing plants.

Typical Industrial Applications:

- Air Tools
- Air Operated Processing Equipment
- Air Operated Packaging Equipment

- Air Operated Knives and Saws
- Food Processing Equipment (H-1)

Performance Benefits:

- Designed specifically for air line lubrication
- Protects against rust
- Provides wear protection
- Complies with FDA 21 CFR 178.3570 H-1

TYPICAL PROPERTIES	TEST METHOD	Air Line FG
ISO Grade	ASTM D2422	32
Viscosity @ 40°C,cSt	ASTM D445	32
Viscosity @ 100°C,cSt	ASTM D445	6.0
Viscosity Index	ASTM D2270	135
Flash Point, °C/°F	ASTM D92	245/473
Pour Point, °C/°F	ASTM D97	-50/-58
Copper Corrosion	ASTM D130	1b
Specific Gravity	ASTM D1298	0.83

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd. New Castle, DE 19720 P.....302-325-9880 F.....302-325-0335 info@ultracheminc.com