

ULTRACLEAN

ROTARY-SCREW COMPRESSOR CLEANER AND SYSTEM FLUSH

Applications:

Ultraclean is a premium quality synthetic fluid designed to dissolve varnish and solubilize sludge from rotary-screw air compressors during operation. It can also be used as a system flush when changing-over from mineral to synthetic oils in order to reduce contamination due to oil carry-over. Regular use of Ultraclean will help you get the most out of your synthetic oil and your compressor by removing varnish and reducing operating temperature.

Typical Industrial Applications:

- Rotary Screw Compressor
- Rotary Vane Compressor
- Centrifugal Compressor

Performance Benefits:

- Solubilizes and removes harmful varnish and “sludge”
- 100% synthetic
- Compatible with mineral oils as well as Ultrachem synthetic oils
- Contains no aromatic solvents or hazardous ingredients
- Contains additives so that it can be used as a lubricant for up to 500 hours
- High flash point
- Caution: May affect some paint finishes, plastics and seals
- USDA H-2 authorized

PROPERTY	TEST METHOD	Ultraclean
ISO Grade	ASTM D2422	32/46
SAE Grade	SAE J-300	10
Viscosity @ 40°C,cSt	ASTM D445	38.5
Viscosity @ 100°C,cSt	ASTM D445	5.4
Viscosity Index	ASTM D2270	59
Flash Point, °C/°F	ASTM D92	224/435
Pour Point, °C/°F	ASTM D97	-42/-44
Copper Corrosion	ASTM D130	1b
Demulsibility	ASTM D1401	Excellent
Specific Gravity	ASTM D1298	0.97

HEALTH & SAFETY

To obtain an MSDS on this or any other Ultrachem product, please contact your representative.

TECHNICAL SUPPORT

To learn more about Ultrachem products and applications please contact us at info@ultracheminc.com



900 Centerpoint Blvd.
New Castle, DE 19720
P.....302-325-9880
F.....302-325-0335
info@ultracheminc.com