

VISCHEM® 352

SYNTHETIC MULTI-PURPOSE GREASE

APPLICATIONS:

Vischem® 352 is a fully synthetic multi-purpose grease formulated for use in a wide variety of applications. Vischem 352 is soft and applies easily; only a thin film is required. Vischem 352 will not wipe off, sling off, or drip off.

TYPICAL INDUSTRIAL APPLICATIONS:

- | | |
|--|--|
| <ul style="list-style-type: none"> ▪ Business Machines ▪ Gear Boxes ▪ Gas Meters ▪ Tools ▪ Bearings ▪ Control Mechanisms ▪ Parking Meters ▪ Timers ▪ Clocks | <ul style="list-style-type: none"> ▪ Speedometers ▪ Potentiometers ▪ Instruments ▪ Counters ▪ Motors ▪ Appliances ▪ Optical Instruments ▪ Recorders ▪ Sound Equipment |
|--|--|

PERFORMANCE BENEFITS:

- Excellent anti-wear properties
- Will not dry out to form gum, sludge, or other deposits
- Longest possible life
- Protects against humidity and prevents rust
- Wide temperature range, -65°F to 300°F

TYPICAL PROPERTIES	TEST METHOD	Vischem 352
NLGI Grade	---	1
Color	Visual	Light Tan
Structure	Visual	Smooth
Penetration Worked (60 strokes)	ASTM D217	330
Unworked	ASTM D217	325
Dropping Point, °C	ASTM D2265	187
Oil Separation, 24 hrs. at 100°C, %	ASTM D6184	6.0
Evaporation, 24 hrs. at 100°C, %	CTM	0.36
Water Washout @ 38°C, %	ASTM D1264	2.1
Base Oil	---	Synthetic